





the Jeopster





SPECIFICATIONS

GENERAL

104" Wheelbase 1781/2" Overall length

8 5/16" (Rear axle) Road clearance

ENGINE

No. of cylinders

63 HP @ 4000 RPM Horsepower

31/6" Bore 43/8" Stroke

106 lb. ft. at 2000 RPM Torque

134.2 cu. in. Displacement

8.5" diam., 72 sq. in. Clutch engagement area

Compression ratio (Standard) 6.48 to 1

Positive crankcase ventilation

Closed cooling system with Cooling system

pressure cap and thermostat-more than adequate

Independent, planar type

for all climates.

4.88 to 1

REAR AXLE RATIO

FRONT SUSPENSION

SPRINGS

All mounted in rubber

Transverse, semi-elliptic Front Conventional, semi-elliptic Rear Rubber inserts insure silent spring action and controlled

shock absorber action.

TIRE SIZE 5.90-15, 4-ply Super Cushion, white side-walls

BRAKES, SERVICE 133 sq. in.

Reduces engine revolutions OVERDRIVE

30%

FRAME Box section frame with

"X" reinforcement

STANDARD EQUIPMENT ON THE 'JEEPSTER', AT NO EXTRA COST, ARE THE FOLLOWING FEATURES:

Overdrive transmission Vacuum booster type fuel pump Luxurious pipe trim upholstery

Dual windshield wipers

Dual sun visors Locking glove box

Spare tire lock Front bumper guards Deluxe steering wheel and

horn ring

Wheel trim rings Dual horns

Inside rear view mirror

Specifications subject to change without notice,